

COBRA™

S E R I E S



COBRA™

The New Way® Cobra™ is the contractor's choice with its outstanding compaction in a lightweight 20 yd³ body. Add in the Cobra's large 3 yd³ hopper, available in 9 to 25 yd³ capacities, and a variety of container handling options, and you'll understand why the Cobra™ is setting the standard in the industry.



COBRA™ SPECIFICATIONS

GENERAL SPECIFICATIONS (STANDARD)

Model	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
Body Capacity	11 yd ³	13 yd ³	16 yd ³	18 yd ³	20 yd ³	25 yd ³
Body Width (A)	96"	96"	96"	96"	96"	96"
Body Length (B)	185.5"	204"	217.5"	224"	250"	280"
Body Height (C)	72"	72"	84"	84"	84"	93"
* Approx. Body Weight	9,650 lbs.	10,012 lbs.	10,323 lbs.	10,760 lbs.	11,227 lbs.	12,200 lbs.
Hopper Capacity	2.5 yd ³	2.5 yd ³	3 yd ³	3 yd ³	3 yd ³	3 yd ³
Hopper Opening Width	74"	74"	74"	74"	74"	74"
Hopper Load Height	Frame	Frame	Frame	Frame	Frame	Frame
Hopper Cycle Time (sec)	26-30	26-30	26-30	26-30	26-30	26-30

HYDRAULIC CYLINDER SPECIFICATIONS (STANDARD)

Model	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
Slide Cylinders (2)	4"	4"	4.5"	4.5"	4.5"	4.5"
Sweep Cylinders (2 Each)	5"	5"	5"	5"	5"	5"
Tailgate Cylinders (2 Each)	3.5"	3.5"	4"	4"	4"	4"
Ejection Cylinder (Telescopic)	3 Stage 5.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"	4 Stage 6.5"

MINIMUM CHASSIS SPECIFICATIONS (STANDARD)

Model	11 RL	13 RL	16 RL	18 RL	20 RL	25 RL
** Minimum GVWR	27,500 lbs.	29,000 lbs.	31,000 lbs.	33,000 lbs.	33,000 lbs.	56,000 lbs.
Recommended Cab to Axle	84"	102"	114"	120"	140"	160"CT ‡

* Approximate Body Weight empty and exclusive of options

** Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

‡ Tandem Required

BODY CONSTRUCTION (High Tensile Steel)

- Roof	10 GA	80K GR
- Sides	10 GA	80K GR
- Floor (sides)	10 GA	80K GR
- Floor (center)	1/4"	50K GR
- Ejection Panel	10 GA	50K GR
- Sweep Panel	1/4"	50K GR
- Tailgate (upper)	10 GA	50K GR
- Tailgate (lower)	7 GA	50K GR
- Hopper Floor (back)	1/4"	100K GR
- Slide Panel	7 GA	50K GR
- Hopper Floor	1/4"	50K GR

HYDRAULIC SYSTEMS

	US	Metric
- Oil Reservoir	45 gal	170 L
- Oil Flow w/std Pump	29 GPM	110 LPM
- Max. Oper. Pressure	2,300 PSI	15,858 KPA
- Max. Oper. Pressure (9yd, 11yd, 13yd)	2,500 PSI	

All models and specifications subject to change.

Visit us online at newwaytrucks.com for the latest updates.

HYDRAULIC SYSTEMS (Cont.)

- Engine RPM for STD GPM 1,200-1,500
- Hydraulic Hoses 4 to 1 Burst
- Hydraulic Filter 10 micron

STANDARD EQUIPMENT

- Semi Automatic Cycling
- Accelerator Kit
- Auto-Lock Tailgate
- Back Up Alarm
- All LED Lights
- Hydraulic Tank Temperature Gauge
- Right Side Hydraulic Tank Access Port
- ICC Lights and Reflectors
- Sight Gauge on Oil Tank
- Chrome Cylinder Rods
- Side Access Door
- Driver Alert Buzzer
- Tailgate Ajar Indicator
- Upper Rear Lights
- Adjustable Riding Steps
- Prime Paint
- Pump
- Color Rear Vision Camera System

OPTIONAL EQUIPMENT

- Special Lighting
- PTO
- Finish Paint-Hmron Elite
- Container Lifts
- Pack at Low Idle
- Hopper Liners
- Upgraded Steel Packages
- Body Scale Systems
- CNG Powered

AUTHORIZED DEALER



a quality product of **McLaughlin** FAMILY COMPANIES

P.O. Box 336 · 101 State Street · Scranton, IA 51462

T 800 831 1858 · F 712 652 3399 · www.newwaytrucks.com